



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/496,607	02/02/2000	Sarit Neter	YMEDIA.001A	6486
28112	7590	10/12/2005	EXAMINER	
GEORGE O. SAILE & ASSOCIATES 28 DAVIS AVENUE POUGHKEEPSIE, NY 12603			MOE, AUNG SOE	
			ART UNIT	PAPER NUMBER
			2685	
DATE MAILED: 10/12/2005				

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

09/496,607

Applicant(s)

NETER, SARIT

Examiner

Aung S. Moe

Art Unit

2685

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 17 August 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1,3,29,38 and 43-48 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1,3,29,38 and 43-48 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Arguments

1. Applicant's arguments with respect to claims 1, 3, 29, 31, 38 and 43-48 have been considered but are moot in view of the new ground(s) of rejection.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

1. Claims 1, 3, 38, 43, 45 and 47 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hashimoto (U.S. 4,768,085) in view of Wilder et al. (U.S. 5,262,871) and Kozlowski et al. (U.S. 6,532,040 B1).

Regarding claim 1, Hashimoto '085 discloses a color imaging system providing on-the-fly color interpolation using analog signals to reconstruct colors during sensor readout (Fig. 3, col. 3, lines 55-68), the imaging system comprising:

an array of pixel sensor elements wherein at least part of the array is arranged in rows and columns (Fig. 1; col. 3, lines 40+);

a color filter including a plurality of color filter components organized in a predefined pattern, the color filter overlaying at least a portion of the array (i.e., noted from Figs. 1 and 4 that the color filter components are organized in a predefined pattern);

Art Unit: 2685

a readout control circuit coupled to the array (i.e., noted the element 2a as shown in Fig. 2; col. 4, lines 5+);

an array controller coupled to the array (i.e., see Fig. 2; col. 4, lines 5+);

wherein the readout control circuit (2a) and the array controller (2a, 2a1 and 2a2) are configured to simultaneously read out values for a group of pixel elements from two different rows and two pixel elements from two different columns (i.e., Figs. 2, 7 and 12; col. 3, lines 54+, and col. 5, lines 60+) and

to reconstruct color components for at least a first pixel sensor element and a second pixel sensor element using color information (i.e., noted that the G signal is reconstructed from the pixels= signals such as G1 and G2 as shown in Figs. 2 and 3) from other pixels elements (i.e., noted the pixel elements nH/mH as shown in Fig. 1) within at least the first portion of the array while the readout control circuit is reading said first portion of the array (i.e., col. 4, lines 20+ and col. 5, lines 1+).

In addition, it is noted that although Hashimoto '085 shows the readout control circuit (Fig. 2, the elements 2a) generating the specific reading pattern while the readout control circuit enables sub-sampling the sensor array (i.e., see Figs. 1 and 2, noted the Odd/Even sub-sampling read out), Hashimoto '085 does not explicitly stated the readout control circuit capable of sub-sampling (i.e., reading) by skipping pixel elements along horizontal or vertical direction of the array as amended in present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Wilder '871. In particular, Wilder '871 teaches that it is conventionally well-known in the art at the time of the invention was made to program the readout control circuit

Art Unit: 2685

(i.e., noted the readout control circuit as shown in Fig. 1 of Wilder '871) for the purpose of selectively sub-sampling by skipping pixel elements along horizontal or vertical direction to create a lower resolution image (i.e., noted that the groups of pixel elements as shown in Figs. 2 may be selectively sampled by skipping pixel elements along row/column direction of the sensor array during the specific resolution mode as discussed in col. 2, lines 50-55 and col. 6, lines 50+; see col. 3, lines 20+ and col. 6, lines 2+ of Wilder '871).

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Wilder '871, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Wilder '871, since Wilder '871 states at col. 2, lines 50+ that such a modification would achieve high speed data capture rate for high frame rates thereof.

Furthermore, it is noted that although Hashimoto '085 shows the use of a plurality of color amplifiers (i.e., noted from Fig. 3 that each of the amplifiers 3, 4 and 5 are corresponding to one the colors of light), Hashimoto '085 does not explicitly state that the amplifier has a programmable gain and contained within the array of pixel sensors as recited in the present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Kozlowski '040. In particular, Kozlowski '040 teaches in order to suppress the to suppress the temporal and spatial noise, it is conventionally well-known in the art to use a plurality of color amplifiers (i.e., noted the programmable amplifiers 50 of the column buffer 40 as shown in Figs. 3 and 4) each corresponding to one of the colors (i.e., noted from col. 6, lines

Art Unit: 2685

65+, the CMOS sensor array contains R, G and B color filter, thus, R, G and B signals are read out from the pixels array 10 as shown in Figs. 3 and 4) of lights wherein each of the color amplifiers has a programmable gain (i.e., col. 8, lines 23+, col. 9, lines 15+; see Figs. 3 and 4) and contained within the array of pixel sensors (i.e., noted that the programmable amplifier 50 is contained within the pixel circuitry 40 of the sensor array 10 of the CMOS; see Figs. 3 and 4; col. 7, lines 10+ and col. 9, lines 50+) as recited in the present claimed invention.

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Kozlowski '040, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Kozlowski '040, since Kozlowski '040 states at col. 5, lines 5+ that such a modification would normalize the amplified offset signal to suppress the temporal and spatial noise that would otherwise be generated by the column buffer .

Regarding claim 3, Hashimoto '085 discloses wherein the readout control circuit is adapted to perform color interpolation using two pixel sensor elements read out in parallel (i.e., col. 3, lines 60+ and col. 6, lines 14+).

Regarding claim 43, it is noted that Hashimoto '085 does not explicitly states the use of CMOS Sensor, however, Kozlowski '040 teaches that it is conventionally well-known in the art at the time the invention was made to use CMOS sensors in order to realize low read noise (i.e., see col. 6, lines 50-36 of Kozlowski '040). In view of this, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as at least taught by Kozlowski '040, since Kozlowski '040 states at col. 6, lines 30+ that such a modification would achieve low read noise comparable or superior to CCD

Art Unit: 2685

system. In addition, Wilder '871 also teaches that it is well known in the art to use the CCD or CMOS sensor in the camera device (i.e., see col. 10, lines 55+ of Wilder '871).

Regarding claim 45, although Hashimoto '085 teaches the use of a control circuit is programmed to selectively reading groups of pixel elements to create a color reconstruction (i.e., noted Figs. 1 and 2 of Hashimoto '085), Hashimoto '085 does not explicitly state that the readout control circuit is programmed to selectively skip some of the groups of pixel elements to create a lower resolution.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Wilder '871. In particular, Wilder '871 teaches that it is conventionally well-known in the art at the time of the invention was made to program the readout control circuit (i.e., noted the readout control circuit as shown in Fig. 1 of Wilder '871) for the purpose of selectively skip some of the groups of pixel elements to create a lower resolution image (i.e., i.e., noted that the groups of pixel elements as shown in Figs. 2 may be selectively skipped during the specific resolution mode as discussed in col. 6, lines 50+; see col. 3, lines 20+ and col. 6, lines 2+ of Wilder '871).

In addition, Kozlowski '040 also teaches that the readout control circuit of the CMOS sensor can be programmed to selectively skip some of the groups of pixel elements, such that the groups of pixel elements can be selectively readout (i.e., "Windowing" as discussed in col. 10, lines 20+) to create a lower resolution color image reconstruction, and this feature simplifies support electronics to reduce cost and match the needs of the particular communication medium.

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Wilder '871/Kozlowski '040, it would have been obvious to one having

Art Unit: 2685

ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Wilder '871/Kozlowski '040, since Wilder '871 states at col. 2, lines 50+ that such a modification would achieve high speed data capture rate for high frame rates; and Kozlowski '040 further suggests in col. 10, lines 35+ such a modification would reduce cost and match the needs of the particular communication medium (i.e., During teleconferencing the Window around a person's mouth could be supplied more frequently than the entire image out of the sensor).

Regarding claim 38, Hashimoto '085 discloses a color imager (i.e., Figs. 3, 5, 8 and 10) comprising:

a first light sensor which generates a first analog output signal related to the amount of a first color of light sensed (i.e., noted the sensor of the sensor 2 of the imager generates the first analog output signal such that the green signal G1 as shown in Fig. 8 and 9; see col. 6, lines 10+);

a second light sensor which generates a second analog output signal related the amount of said first color of light sensed (i.e., noted the sensor of the sensor 2 of the imager generates the first analog output signal such that the green signal G3 as shown in Fig. 8 and 9; see col. 6, lines 10+);

a third light sensor (i.e., The Blue sensor of the sensor 2) which generates a third analog output signal related to the amount of a second color of light sensed (i.e., noted the sensor of the sensor 2 of the imager generates the third analog output signal such that the blue signal B2 as shown in Fig. 8 and 9; see col. 6, lines 10+);

a fourth light sensor (i.e., The Red sensor of the sensor 2) which generates a fourth analog output signal related to the amount of a third color of light sensed (i.e., noted the sensor of the sensor 2 of the imager generates a fourth analog output signal such that the red signal R as shown in Fig. 8 and 9; see col. 6, lines 10+);

a circuit configured to read out the first, second, third, and fourth analog values at the same time (i.e., col. 3, lines 55-68 and col. 5, lines 60+); and

an interpolation circuit configured to receive said first output signal and said second output signal (i.e., col. 3, lines 55+), wherein said interpolation circuit provides an interpolation signals on the fly based on at least said first analog output signal and said second analog output signal (col. 6, lines 5+).

In addition, it is noted that although Hashimoto '085 shows the readout control circuit (Fig. 2, the elements 2a) generating the specific reading pattern while the readout control circuit enables sub-sampling the sensor array (i.e., see Figs. 1 and 2, noted the Odd/Even sub-sampling read out), Hashimoto '085 does not explicitly stated the readout control circuit capable of sub-sampling (i.e., reading) by skipping pixel elements along horizontal or vertical direction of the array as amended in present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Wilder '871. In particular, Wilder '871 teaches that it is conventionally well-known in the art at the time of the invention was made to program the readout control circuit (i.e., noted the readout control circuit as shown in Fig. 1 of Wilder '871) for the purpose of selectively sub-sampling by skipping pixel elements along horizontal or vertical direction to create a lower resolution image (i.e., noted that the groups of pixel elements as shown in Figs. 2

Art Unit: 2685

may be selectively sampled by skipping pixel elements along row/column direction of the sensor array during the specific resolution mode as discussed in col. 2, lines 50-55 and col. 6, lines 50+; see col. 3, lines 20+ and col. 6, lines 2+ of Wilder '871).

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Wilder '871, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Wilder '871, since Wilder '871 states at col. 2, lines 50+ that such a modification would achieve high speed data capture rate for high frame rates thereof.

Furthermore, it is noted that although Hashimoto '085 shows the use of a plurality of color amplifiers (i.e., noted from Fig. 3 that each of the amplifiers 3, 4 and 5 are corresponding to one the colors of light), Hashimoto '085 does not explicitly state that the amplifier has a programmable gain and contained within the array of pixel sensors as recited in the present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Kozlowski '040. In particular, Kozlowski '040 teaches in order to suppress the to suppress the temporal and spatial noise, it is conventionally well-known in the art to use a plurality of color amplifiers (i.e., noted the programmable amplifiers 50 of the column buffer 40 as shown in Figs. 3 and 4) each corresponding to one of the colors (i.e., noted from col. 6, lines 65+, the CMOS sensor array contains R, G and B color filter, thus, R, G and B signals are read out from the pixels array 10 as shown in Figs. 3 and 4) of lights wherein each of the color amplifiers has a programmable gain (i.e., col. 8, lines 23+, col. 9, lines 15+; see Figs. 3 and 4) and contained within the array of pixel sensors (i.e., noted that the programmable amplifier 50 is

Art Unit: 2685

contained within the pixel circuitry 40 of the sensor array 10 of the CMOS; see Figs. 3 and 4; col. 7, lines 10+ and col. 9, lines 50+) as recited in the present claimed invention.

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Kozlowski '040, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Kozlowski '040, since Kozlowski '040 states at col. 5, lines 5+ that such a modification would normalize the amplified offset signal to suppress the temporal and spatial noise that would otherwise be generated by the column buffer .

Regarding claim 47, please see the Examiner's comments with respect to claim 43 as discussed above.

2. Claims 44 and 48 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hashimoto '085 in view of Wilder '871 and Kozlowski '040 as applied to claims discussed above, and further in view of Lee et al. (U.S. 6,466,265 B1).

Regarding claim 44, although Hashimoto '085 and Kozlowski '040 shows the use of color filter components (i.e., col. 4, lines 5+ of Hashimoto '085; see col. 6, lines 60+ of Kozlowski '040), Hashimoto '085 does not explicitly state the use of a Bayer pattern color filter as recited in the present claimed invention.

However, Lee '265 teaches that it is conventionally well-known in the art at the time of the invention was made to use a Bayer pattern color filter as recited in the present claimed invention (i.e., col. 3, lines 20+ of Lee '265). In view of this, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of

Art Unit: 2685

Hashimoto '085 as taught by Lee '265, since Lee '265 states at col. 1, lines 50+ that such a modification would achieve high pixels output rate for high frame rates thereof.

Regarding claim 48, please see the Examiner's comments with respect to claim 44 as discussed above.

3. Claims 29 and 31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Maenaka et al. (U.S. 5,555,023) in view of Wilder et al. (U.S. 5,262,871) and Kozlowski '040.

Regarding claim 29, Maenaka '023 discloses a method of interpolating color components of an array of pixel sensor elements (col. 3, lines 40+ and col. 6, lines 45+), said method comprising:

reading a first rectangular portion of an array of pixel sensor elements simultaneously, wherein the first rectangular portion includes pixel sensor elements from at least two array columns and two array rows (i.e., Fig. 8; col. 1, lines 45-50, col. 2, lines 45+);

reading a second rectangular portion of the array of pixel sensor elements, wherein the second portion partly overlaps said first portion (i.e., Fig. 8; col. 1, lines 45+ and col. 2, lines 45+); and

reconstructing color components using interpolation for at least a third portion of the array while said third portion of the array is being read (i.e., Figs. 2 and 8-9; col. 2, lines 35+, col. 6, lines 35+ and col. 7, lines 20+), and wherein said interpolation comprises summing values of two or more said pixel sensor elements (i.e., see Fig. 2, the elements 269-270 and col. 6, lines 10-60).

In addition, it is noted that although Maenaka '023 shows the reading of the first and second rectangular portions (i.e., see Fig. 8) is controlled by the readout control circuit (Fig. 1, the elements 30 and 31) generating the specific reading pattern while the readout control circuit is reading the first and second portions of the sensor array (i.e., see Figs. 1, 4 and 8).

Moreover, Maenaka '023 clearly shown in Fig. 8 that the reading of the first and second rectangular portions (i.e., noted the rectangular portion of ODD pixel field and EVEN pixel fields) is by skipping pixel elements (i.e., noted that when the rectangular portion of "B" ODD pixel field is read out, three rows/columns on the sensor array "A" is skipped to produce 3 x 3 ODD filed, and the same goes for the pixel block "C" thru "E" as well) along horizontal or vertical directions of said array (i.e., noted input sensor array A of Fig. 8).

Furthermore, it is noted that Maenaka '023 does not explicitly states the use of CMOS Sensors, however, Wilder '871 teaches that it is conventionally well-known in the art at the time the invention was made to use CMOS Sensors in the camera to achieve a maximum speed of operation and a minimum power dissipation thereof (i.e., see col. 10, lines 30+ of Wilder '871). In view of this, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Maenaka '023 as taught by Wilder '871, since Wilder '871 states at column 10, lines 30+ that such a modification would provide a maximum speed of operation and a minimum power dissipation in the imaging system.

Moreover, it is noted that although Maenaka '023 shows the use of a plurality of color amplifiers (noted the amplifiers located within the sensor 1) for reading of said first and second portions (i.e., See Fig. 8 of Maenaka '023), Maenaka '023 does not explicitly show plurality of

Art Unit: 2685

color amplifiers placed within the array of pixel sensor elements as recited in present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Kozlowski '040. In particular, Kozlowski '040 teaches in order to suppress the to suppress the temporal and spatial noise, it is conventionally well-known in the art to use a plurality of color amplifiers (i.e., noted the programmable amplifiers 50 of the column buffer 40 of the pixel circuitry as shown in Figs. 3 and 4; also noted that each pixel 10 in a column contains a column buffer 40, thus, row N x column M of CMOS sensor must contain plurality of color amplifiers as required by present claimed invention) and contained within the array of pixel sensors (i.e., noted that the programmable amplifier 50 is contained within the pixel circuitry 40 of the sensor array 10 of the CMOS; see Figs. 3 and 4; col. 7, lines 10+ and col. 9, lines 50+) as recited in the present claimed invention. In addition, Kozlowski '040 teaches that plurality of color amplifiers (40/50) of MxN array is used during the reading process of particular portions (i.e., noted that "Windowing" for reading a selective group of pixels as discussed in col. 10, lines 25+ and reading Row N, and Row N+1 of all of the pixels 10 from the sensor as shown in Fig. 5)

In view of the above, having the system of Hashimoto '085 and then given the well-established teaching of Kozlowski '040, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Hashimoto '085 as taught by Kozlowski '040, since Kozlowski '040 states at col. 5, lines 5+ that such a modification would normalize the amplified offset signal to suppress the temporal and spatial noise that would otherwise be generated by the column buffer .

Art Unit: 2685

Regarding claim 31, Maenaka '023 discloses wherein reconstructing color components (i.e., the R, G and B signal as shown in Fig. 8) using interpolation is performed in real-time (i.e., noted the color components are interpolated as read out from the image sensor in real-time as claimed).

4. Claim 46 is rejected under 35 U.S.C. 103(a) as being unpatentable over Maenaka '023 in view of Wilder '871 and Kozlowski '040 as applied to claims discussed above, and further in view of Lee at al. (U.S. 6,466,265).

Regarding claim 46, although Maenaka '023 shows the use of color filter components (i.e., Fig. 8 of Maenaka '023), Maenaka '023 does not explicitly state the use of a Bayer pattern color filter as recited in the present claimed invention.

However, Lee '265 teaches that it is conventionally well-known in the art at the time of the invention was made to use a Bayer pattern color filter as recited in the present claimed invention (i.e., col. 3, lines 20+ of Lee '265).

In view of this, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Maenaka '023 as taught by Lee '265, since Lee '265 states at col. 1, lines 50+ that such a modification would achieve high pixels output rate for high frame rates thereof.

Art Unit: 2685

Conclusion


5. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Neter '568 is related to the present claimed invention.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Aung S. Moe whose telephone number is 571-272-7314. The examiner can normally be reached on Flex.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward F. Urban can be reached on 571-272-7899. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).


Aung S. Moe
Primary Examiner
Art Unit 2685

A. Moe
September 30, 2005